

- [54] **SPIN COATING PROCESS**
- [75] Inventors: **Masamichi Sato; Itsuo Fujii**, both of Asaka, Japan
- [73] Assignee: **Fuji Photo Film Co., Ltd.**, Minami-ashigara, Japan
- [21] Appl. No.: **785,886**
- [22] Filed: **Apr. 8, 1977**
- [30] **Foreign Application Priority Data**
Apr. 8, 1976 [JP] Japan 51-39690
- [51] **Int. Cl.²** **B05D 3/12**
- [52] **U.S. Cl.** **96/67; 96/35.1; 96/86 P; 427/240; 427/273; 427/331; 427/335; 427/336; 427/337**
- [58] **Field of Search** 427/240, 331, 273, 335-337; 96/67, 35.1

2,563,417	4/1947	Pessel	427/273
2,987,415	6/1961	Taggett	427/273
3,936,301	2/1976	Schneider	96/35.1

Primary Examiner—Ronald H. Smith
Assistant Examiner—Janyce A. Bell
Attorney, Agent, or Firm—Sughrue, Rothwell, Mion, Zinn and MacPeak

[57] **ABSTRACT**

A process of spin coating a coating composition on the surface of a base plate, comprising supplying a material which is compatible with the coating composition, in either a liquid or vapor form, to the opposite surface of the base plate to the surface on which the coating composition has been supplied (hereinafter "back surface" or "back side") while rotating the base plate to remove the coating composition flowing to the back surface or to the edge portion of the plate. The material compatible with the coating composition may be applied to the surface of the base plate at the periphery thereof to reduce or remove the coating composition there.

- [56] **References Cited**
- U.S. PATENT DOCUMENTS**
- 10,789 4/1854 Field 427/240
- 1,744,463 1/1930 Gravel 427/273
- 2,110,282 3/1938 Amsel 427/240

14 Claims, 8 Drawing Figures

